

Engineered Oak Wide Plank 240 x 15/4 mm x 2200mm.

This stunning new De Marque Wide Plank Collection is available with a gorgeous palette of 6 pre-finished colours guaranteed to provide warmth and charm to any interior.

The planks are manufactured from sustainable timber combining a 4 mm solid European Oak wear layer engineered onto a 11 mm multi-ply, hardwood substrate. This trusted method of construction provides a long wearing, stable and durable engineered floor with a finished thickness of 15mm.

Please consult with your supplier for specific site install guidelines prior to installation.

De Marque Wide Plank Collection			240 x 15/4 mm x 2200mm T&G	
Colour	Scotia	Trim	Sqm/Ctn	Micro-Bevel V4
Copper Brown	Capital	Walnut	2.112m2	Yes
Dusk Grey	Misty Cove	Moon	2.112m2	Yes
French Lace	Ghost Gum	Parana	2.112m2	Yes
Matterhorn	Blackbutt	Latte	2.112m2	Yes
Polar Ice	Parana	Parana	2.112m2	Yes
Valley Oak	Zermatt	Sunshine	2.112m2	Yes

Key Features;

Engineered to exacting standards. Extremely stable, wear layer can be refurbished and rejuvenated when required. Suitable for residential, multi-residential and light commercial installation.

Installation; for an optimum outcome, direct adhesive fix recommended, full trowel spread method bonded to a secure, flat & dry substrate. A compatible Moisture Barrier & Adhesive (same brand) required for direct fix installation.

Multi-purpose, 3 in 1 or similar adhesives are not covered by our warranty.

Description; Engineered European Oak, Multi-Ply Structural Core, Tongue & Groove. **VOC Emissions; E1.**

Grade & Surface; A/B/C Grade, contains knots and split defects that are filled and patched to compliment surface colour and character. Pre-finished, Matte PU coating. Light wire brush.

Profile; T&G - Micro Bevelled Edges, 4 sides.

Size & Length; 240mm width x 15/4 mm thickness, 2200mm length - 2.112m2 / Carton

Fire Test Data; Test Method AS/ISO9239.1.Critical Radiant Flux, kW/m2.

7.5 kW/m2 Mean Smoke Development, 17 percent minutes.

Slip Resistance; In accordance with AS/NZS 4586 2013, **P3.**

Please consult with your supplier for specific site install guidelines or contact: info@preferencefloors.com.au
www.preferencefloors.com.au

Adelaide (SA)

t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)

t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)

t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)

t +61 2 9738 1188
sales@preferencefloors.com.au